



# Rolleiflex T



The lens of the Rolleiflex T is the world-famous Carl Zeiss Tessar for outstanding quality.

This Rollei is available with or without exposure meter. The meter gives accurate readings (a switch selects one of the two measuring ranges) to show the correct exposure value. But you can also fit the exposure meter at any time later on. (Incidentally, this is quite a simple matter which your photo dealer will also be glad to do for you.)

To sum up: A multi-size camera with high-quality lens, simple and convenient operation and plenty of scope with accessories.




You are no doubt familiar with the idea of the Rollei system from our colour catalogue "Rollei 2 1/4 x 2 1/4 inches — its assets and yours". This listing of features is a special supplement for it.


Rolleiflex T (Tessar f/3.5)	580 011
without exposure meter .....	580 021
with exposure meter .....	970 320
Ever-ready case .....	208 100
16-exposure mask set .....	208 700
Rolleikin outfit .....	580 060
Exposure meter for installation .....	




1



2



3



Lenses:

Taking lens: 75 mm. Carl Zeiss Tessar f/3.5, four elements, angle of view 56°. Finder lens: 75 mm. Heidosmat f/2.8. Size I bayonet mount (6 x 6) for accessories.

Finder:

Interchangeable folding hood with 2.5 x magnifier. Built-in frame finder. Ruled focusing screen. Automatic parallax compensation for all picture sizes.

Exposure meter:

Needle-matching system, indicates exposure values (Fig. 1). Basic camera available with or without two-range exposure meter; meter can be built in subsequently.

Shutter:

Synchro-Compur MXV, M- and X-synchronized for flash. Self-timer with approximately 10 seconds delay. Exposure values can be set from 1 to 18, with cross-coupled aperture-speed selection. Shutter speed range 1 to 1/500 second. Time exposures shown from 2 to 60 seconds (for shots at low exposure values). Aperture range from f/3.5 to f/22. Single lever operation (Fig. 2) for shutter speeds and apertures; individual settings also possible. Common peep window for shutter speed and aperture.

Focusing:

Film transport crank (Fig. 3) also tensions the shutter. Double exposure and blank frame lock. Body release with safety lock and cable release socket.

Film transport:

Focusing knob with film type indicator. Unaided focusing range from infinity to 3 feet (0.9 metres). Depth of field scale.

Picture Sizes:

Film transport crank (Fig. 3). Film counter automatically switches over from 12 to 16 exposures or vice versa.

Dimensions and Weight:

2 1/4 x 2 1/4 inches (6 x 6 cm.) on size 120 roll film; also 1 5/8 x 2 1/8 inches (4 x 5.5 cm.) and 1 5/8 x 1 5/8 inches (4 x 4 cm.) with the 16-exposure mask set. Further, 24 x 36 mm. on 35 mm. miniature film with the Rolleikin outfit.

Special Accessories:

Height: 6 inches (14.8 cm.). Width: 4 1/2 inches (11.2 cm.). Depth: 3 3/4 inches (9.7 cm.). Weight: 36 ounces (1020 grams). Ever-ready case with removable front. 16-exposure mask set. Rolleikin outfit. Exposure meter for installation.

Rollei-Werke  
Franke & Heidecke  
Braunschweig  
Germany

**Rollei**

Your photo dealer will be glad to show you the Rolleiflex T.