The top performance value in a compact precision package.



It's the low cost Rollei 35, the world's most popular Rollei of recent years. It's small, about the size of a pack of cigarettes! Just 9½ ounces of precision. Your customers will love this easy-to-take-it-with-you 35mm . . . It has a high definition, wide angle precision lens that makes a rangefinder unnecessary. And it's packed with every picture-taking convenience for top results.



Technical Data

- Camera Type: Full frame 35mm miniature.
- Picture Format: 24 x 36mm.
- Lens: 40mm Triotar* f/3.5 lens (in retractable barrel) for wide angle coverage. 57° angle of view.
- Focusing range: 3 ft. (0.9 meter) to infinity.
- Shutter: Prontor leaf shutter for compact design; speeds 1/30 to 1/500, B.

- Flash Outlet: Hot shoe contact at all shutter speeds.
- **Exposure:** Built-in selenium exposure meter.
- Film Speed Range: 25 to 1600 ASA.
- Viewfinder Data: Engraved bright line frame with parallax marks.
- Film Transport: Rapid winding lever with 180° swing.

Release:

Release button with cable release socket.

- Automatic Frame Counter: Resets to 0 when back is removed.
- Rewind: Crank in camera base.
 - Size:
 - 3.8 x 2.3 x 1.3 inches (97 x 58 x 32mm).
- Weight: 9 1/2 ounces (270 grams).
- * Made by Rollei under license from Carl Zeiss, Oberkochen, West Germany.

Rollei
35TThe original tiny full-frame 35mm,
and a technical marvel.

A precision masterpiece, the Rollei 35 T is the ideal camera for general, everyday use. The first truly small full-frame 35mm, it's the perfect take-along camera because it has the

essentials for fine performance without cumbersome bulk and technical complexity. The Rollei 35 has swept the world in popularity and made photo history.



Technical Data

- Camera Type: Full-frame 35mm compact.
- Picture Format: 24 x 36mm.
- Lens: Retractable, 40mm, f/3.5 Tessar with click stops for aperture settings from f/3.5 to f/22; 57°
- angle of view.
 Lens Focusing Range:
 3 feet to infinity; zone focus ranges marked in red.
- Shutter: Compur with settings from 1/2 to 1/500 sec. and bulb.
- Exposure Control: CdS exposure meter with matchneedle system coupled to aperture, shutter and film speed controls.

- Film Speed Range: ASA 25 to 1600.
- EV Range: 4.5 to 18.
- Flash Synchronization: Hot shoe contact, at all speeds.
 Shutter Belease:
- Shutter Release: Recessed button on top with cable release socket.
- Film Winding and Loading: Accepts any standard 35mm film cartridge; film advances by 180° lever on top; rewind crank in camera bottom; frame counter counts up from 1 to 36, automatically returns to zero when back is removed.
- Viewfinder Data: Engraved bright frame showing field of view in oversized finder
- window. • Size: 1 1/4 x 3 3/4 x 2 3/8 inches.
- Weight: 13 ounces.
- Other Features:

Fitting for wrist strap and neck strap; camera available in chrome and black leatherette or all black finish; supplied with case, wrist strap, lens cap.

Accessories:

Soft leather case; rigid leather everready case; neckstrap; lens hood; filters; special brackets for Rollei flash units adapts hot shoe to PC connection.



The compact full-frame 35mm with a remarkable new lens.



With its specially designed, multi-coated Rollei HFT[®] Sonnar f/2.8 lens, this full-frame Rollei 35S rates as super-camera. The Sonnar formula and HFT[®] coating set a high in picture

quality. Contrast is better, colors more saturated, light transmission increased, lens flare and reflections decreased. And even at the widest apertures, superb quality is maintained.



Technical Data

- Camera Type: Full frame 35mm miniature.
- Picture Format: 24 x 36mm.
- Lens:

Retractable, 5 element, 40mm f/2.8 Rollei HFT® Sonnar* with multicoating; filter M30.5 x 0.5 screw in; aperture range f/2.8 to f22; angle of view 57°

- Lens Focusing Range: 3 feet to infinity; zone focus ranges marked in red.
- Shutter: Compur with settings from 1/2 to
- 1/500 sec. and bulb. • Shutter Release:

Recessed button on top with cable release socket.

* Made by the Rollei group under license from Carl Zeiss, Oberkochen, West Germany.

- Exposure Control: CdS exposure meter with match needle system coupled to aperture, shutter and film speed dials.
- Film Speed Range: ASA 25 to 1600.
- EV Range: 4 to 18.
- Flash Synchronization: Hot shoe contact, at all shutter speeds.
- Film Winding and Loading: Accepts any standard 35mm film cartridge; film advances by 180° lever on top; rewind crank in camera bottom; frame counter up from 1 to 36, automatically returns to zero when back is opened.
- Viewfinder Data: Engraved bright line frame with parallax marks.

- Size: 1 1/4 x 3 3/4 x 2 3/8 inches.
- Weight: 13 ounces.
- Exposure Meter Battery: Single, 1.35 volt cell (PX 625 or equivalent).
- Other Features: Loop for wrist strap; tripod socket (1/4-20 bushing); camera available in chrome and black leatherette or all black finish.

Accessories:

Soft pouch case; special brackets for Rollei flash units provide adapter for hot shoe to PC connection.

Rollei
B35, 35T, 35SAccessories
for Rollei compact 35's.



SOFT CASE

EVEREADY CASE

COMBI CASE, SOFT holds Rollei 35/B35 w/E15, E15B, E19BC, 121BC or 128BC attached.

NECK STRAP

FOLDING LENS HOODS

MEDIUM YELLOW FILTERS ORANGE FILTERS UV HAZE FILTERS (also for color pictures).

R 1.5 COLOR CORRECTION FILTERS (Skylight—for color pictures).

LENS CAPS, replacement.

Rollei 35

Rollei 35-E15 Combi Case



ROLLEI IS NOW MAKING AVAILABLE A NEW SOFT LEATHER CARRY CASE FOR THE ROLLEI 35-E15 FLASH COMBINATION. THE NEW CASE IS OF SOFT BLACK LEATHER WITH A BLACK NYLON ZIPPER. IT HAS A REINFORCED OPENING TO ALLOW THE WRIST STRAP OF THE ROLLEI 35 TO PROTRUDE, SO THAT IT MAY BE CARRIED WHILE IN THE CASE, IN THE SAME MANNER YOU WOULD CARRY IT OUTSIDE THE CASE. THE NEW CASE ALSO ACCOMMODATES A SINGLE CAN OF 35MM FILM IN THE SPACE BETWEEN THE E15 FLASH AND THE SIDE-WALL OF THE CASE.

THE CASE WILL ALSO ACCOMMODATE THE B35 IN COMBINATION WITH THE E15.

ROLLEI 35-E15 COMBI CASE Cat. No. 03513